




INNER RINGS



JR



JR.JS1




JRZ.JS1


Shaft Dia. mm in	d mm in	F ₁ ¹⁾ mm in	B mm in	F _{max} mm in	Inner Ring Designation	Approx. kg lb
15 0.5906	15 0.5906	20 0.7874	23 0.908	0.3 0.01	JR15x23	0.025 0.055
	15	20	26	0.3	JR15x26	0.038 0.082
	17	20	16.5	0.3	JR17x20-16.5	0.011 0.024
	17	20	19	0.3	JR17x20	0.014 0.031
	17	20	20.5	0.3	JR17x20-20.5	0.014 0.031
	17	20	26.5	0.3	JR17x26-26.5	0.021 0.046
	17	21	16	0.3	JR17x21-16	0.015 0.033
	17	21	19	0.3	JR17x21-19	0.019 0.043
	17	22	13	0.3	JR17x22-13	0.015 0.033
	17	22	16	0.3	JR17x22-16	0.019 0.042
	17	22	16	0.3	JR17x22-16-1S1	0.019 0.042
	17	22	16	0.3	JR17x22-16-1JS1	0.019 0.042
	17	22	20	0.3	JR17x22-20	0.028 0.062
	17	22	26	0.3	JR17x22-26	0.021 0.046
	17	22	32	0.3	JR17x22-32	0.038 0.084
20 0.7874	20 0.7874	24 0.9449	16 0.630	0.3 0.01	JR20x16	0.018 0.040
	20	24	20	0.3	JR20x20	0.022 0.049
	20	25	16	0.3	JR20x25-16	0.022 0.049
	20	25	16	0.3	JR20x25-16-1S1	0.022 0.049
	20	25	17	0.3	JR20x25-17	0.023 0.051
	20	25	18	0.3	JR20x25-18-1S1	0.025 0.055
	20	25	20	0.3	JR20x25-20	0.028 0.062
	20	25	20.5	0.3	JR20x25-20.5	0.029 0.064
	20	25	26	0.3	JR20x25-26	0.036 0.079

¹⁾ Inner rings for metric full complement needle roller bearings are produced with outside diameter tolerance g5


INNER RINGS



JR



JR.JS1



JRZ.JS1

Shaft Dia. mm in	d mm in	F ₁ ¹⁾ mm in	B mm in	F _{max} mm in	Inner Ring Designation	Approx. kg lb
20 0.7874	20 0.7874	25 0.9843	26.5 1.043	0.3 0.01	JR20x26.5	0.037 0.082
	20	25	30	0.3	JR20x30	0.042 0.093
	20	25	32	0.3	JR20x32	0.044 0.097
	20	25	38.5	0.3	JR20x38.5	0.054 0.119
	22	26	16	0.3	JR22x16	0.019 0.042
	22	26	20	0.3	JR22x20	0.023 0.051
	22	28	17	0.3	JR22x28-17	0.030 0.066
	22	28	20.5	0.3	JR22x28-20.5	0.038 0.084
	22	28	30	0.3	JR22x30	0.056 0.122
25 0.9843	25 0.9843	1.1224 1.181	20 0.787	0.3 0.01	JR25x20	0.021 0.046
	25	29	30	0.3	JR25x30	0.040 0.088
	25	30	16	0.3	JR25x30-16	0.027 0.060
	25	30	16	0.3	JR25x30-16-1S1	0.027 0.060
	25	30	17	0.3	JR25x30-17	0.028 0.062
	25	30	18	0.3	JR25x30-18-1S1	0.031 0.068
	25	30	20	0.3	JR25x30-20	0.034 0.075
	25	30	20.5	0.3	JR25x30-20.5	0.035 0.077
	25	30	26	0.3	JR25x30-26	0.044 0.097
	25	30	26.5	0.3	JR25x30-26.5	0.045 0.099
	25	30	30	0.3	JR25x30-30	0.051 0.112
	25	30	32	0.3	JR25x30-32	0.054 0.119
	25	30	38.5	0.3	JR25x38.5	0.066 0.146
28 1.1024	28 1.1024	1.2598 0.869	17 0.67	0.3 0.01	JR28x17	0.028 0.062
	28	32	20	0.3	JR28x20	0.030 0.066

¹⁾ Inner rings for metric full complement needle roller bearings are produced with outside diameter tolerance g5

Continued on next page