







INNER RINGS



Shaft Dia.	d	F11	B	F _{max}	Inner Ring Designation	Approx. Wt.
mm	mm	mm	mm	mm		kg
in	in	in	in	in		lb
45	45	52	23	0.6	JR25x45x23JS1	0.096
1.7717	1.7717	2.0472	0.909	0.02		0.212
45	45	52	40	0.6	JR40x45x40	0.167
1.7717	1.7717	2.0472	1.575	0.02		0.368
45	45	55	29	1	JR45x45x29	0.133
1.7717	1.7717	2.1654	0.797	0.04		0.293
45	45	55	29	1	JR45x45x29JS1	0.133
1.7717	1.7717	2.1654	0.797	0.04		0.293
45	45	55	22	1	JR45x45x22	0.139
1.7717	1.7717	2.1654	0.866	0.04		0.308
45	45	55	44	1	JR45x45x44	0.247
1.7717	1.7717	2.1654	1.735	0.04		0.546
50	50	55	29	0.3	JR40x50x29	0.065
1.9685	1.9685	2.1654	0.797	0.01		0.143
50	50	55	25	0.6	JR40x50x25	0.081
1.9685	1.9685	2.1654	0.984	0.02		0.179
50	50	55	25	0.6	JR40x50x25	0.113
1.9685	1.9685	2.1654	0.984	0.02		0.248
50	50	55	40	0.3	JR40x50x40	0.130
1.9685	1.9685	2.1654	1.575	0.01		0.287
50	50	58	22	0.6	JR40x50x22	0.117
1.9685	1.9685	2.2825	0.866	0.02		0.258
50	50	58	23	0.6	JR40x50x23JS1	0.122
1.9685	1.9685	2.2825	0.909	0.02		0.269
50	50	58	40	0.6	JR40x50x40	0.213
1.9685	1.9685	2.2825	1.575	0.02		0.470
50	50	60	29	1	JR40x50x29	0.155
1.9685	1.9685	2.3622	0.797	0.04		0.342
50	50	60	29	1	JR40x50x29JS1	0.155
1.9685	1.9685	2.3622	0.797	0.04		0.342
50	50	60	25	1	JR40x50x25	0.170
1.9685	1.9685	2.3622	0.984	0.04		0.375
50	50	60	40	1	JR40x50x40	0.310
1.9685	1.9685	2.3622	1.575	0.04		0.683
55	55	60	25	0.6	JR45x55x25	0.088
2.1654	2.1654	2.3622	0.984	0.02		0.194
55	55	60	25	0.6	JR45x55x25	0.124
2.1654	2.1654	2.3622	0.984	0.02		0.273
55	55	63	25	1	JR45x55x25	0.141
2.1654	2.1654	2.4803	0.984	0.04		0.311
55	55	63	45	1	JR45x55x45	0.286
2.1654	2.1654	2.4803	1.772	0.04		0.631
55	55	65	30	1	JR45x55x30	0.222
2.1654	2.1654	2.5591	1.181	0.04		0.489
55	55	65	60	1	JR45x55x60	0.444
2.1654	2.1654	2.5591	2.362	0.04		0.975
60	60	68	25	0.6	JR50x60x25	0.153
2.3622	2.3622	2.6772	0.984	0.02		0.337

(1) Inner rings for metric full complement needle roller bearings are produced with outside diameter tolerance g5

INNER RINGS



Shaft Dia.	d	F11	B	F _{max}	Inner Ring Designation	Approx. Wt.
mm	mm	mm	mm	mm		kg
in	in	in	in	in		lb
60	60	68	25	0.6	JR50x60x25	0.229
2.3622	2.3622	2.6772	0.984	0.02		0.505
60	60	68	45	1	JR50x60x45	0.284
2.3622	2.3622	2.6772	1.772	0.04		0.626
60	60	70	25	0.984	JR50x70x25	0.209
2.3622	2.3622	2.7559	0.984	0.04		0.461
60	60	70	30	1	JR50x70x30	0.240
2.3622	2.3622	2.7559	1.181	0.04		0.529
60	60	70	60	1	JR50x70x60	0.480
2.3622	2.3622	2.7559	2.362	0.04		1.058
65	65	72	25	1	JR55x72x25	0.143
2.5591	2.5591	2.8346	0.984	0.04		0.315
65	65	72	45	1	JR55x72x45	0.266
2.5591	2.5591	2.8346	1.772	0.04		0.586
65	65	72	25	0.6	JR55x72x25	0.170
2.5591	2.5591	2.8346	0.984	0.02		0.375
65	65	72	25	0.6	JR55x72x25	0.240
2.5591	2.5591	2.8346	0.984	0.02		0.529
65	65	75	28	1	JR55x75x28	0.240
2.5591	2.5591	2.9528	1.102	0.04		0.529
65	65	75	30	1	JR55x75x30	0.260
2.5591	2.5591	2.9528	1.181	0.04		0.573
65	65	75	60	1	JR55x75x60	0.520
2.5591	2.5591	2.9528	2.362	0.04		1.146
70	70	80	25	1	JR60x80x25	0.229
2.7559	2.7559	3.1496	0.984	0.04		0.505
70	70	80	30	1	JR60x80x30	0.270
2.7559	2.7559	3.1496	1.181	0.04		0.595
70	70	80	25	1	JR70x80x25	0.320
2.7559	2.7559	3.1496	0.984	0.04		0.702
70	70	80	54	1	JR70x80x54	0.500
2.7559	2.7559	3.1496	2.125	0.04		1.102
70	70	80	60	1	JR70x80x60	0.556
2.7559	2.7559	3.1496	2.362	0.04		1.226
75	75	85	25	1	JR75x85x25	0.240
2.9528	2.9528	3.3465	0.984	0.04		0.529
75	75	85	30	1	JR75x85x30	0.289
2.9528	2.9528	3.3465	1.181	0.04		0.637
75	75	85	35	1	JR75x85x35	0.338
2.9528	2.9528	3.3465	1.379	0.04		0.745
75	75	85	54	1	JR75x85x54	0.530
2.9528	2.9528	3.3465	2.125	0.04		1.188
80	80	90	25	1	JR80x90x25	0.260
3.1496	3.1496	3.5433	0.984	0.04		0.573
80	80	90	30	1	JR80x90x30	0.306
3.1496	3.1496	3.5433	1.181	0.04		0.675
80	80	90	35	1	JR80x90x35	0.355
3.1496	3.1496	3.5433	1.379	0.04		0.783

(1) Inner rings for metric full complement needle roller bearings are produced with outside diameter tolerance g5

Continued on next page